

Sentry SMD-N4 Mobile DVR



Features

- ⚡ 4 Channel Embedded DVR
- ⚡ Anti-Vibration, Anti-Shock Mounted Case and Hard Drive for Maximum Reliability
- ⚡ 120 Frames/Sec Real-Time Display and Recording
- ⚡ Manages Storage and Recycles Space Automatically
- ⚡ Remote Access by LAN or Internet
- ⚡ Fast, High Quality Remote Transmission
- ⚡ Vehicle Status Sensor Displays and Records Vehicle Speed, Turn Signals and Brake Signals on Video

Description

The Sentry SMD-N4 Mobile DVR was designed to meet demanding security applications such as public transportation, law enforcement and military. The SMD-N4 is contained in a small, rugged, vibration and shock resistant case, produces MPEG4 high-resolution video at 120 fps (real-time), allows recorded video to be quickly exported through its USB port and offers a choice of recording options.

The Sentry SMD-N4 Mobile DVR supports up to 4 channels of video, 2 channels of audio and gives users the option of selecting recording resolutions from CIF (352x240) to D1 (704x480). The removable hard drive stores recorded video and can be removed and connected to a standard PC to view recorded video. Networking and remote access can be accomplished through its standard LAN Port. This mobile solution comes complete with everything required for simple installation.

Sentry Security Systems Inc. mobile solutions are currently being used in the following applications:

- Law Enforcement - Patrol Cars
- Military - Tanks
- Emergency – Ambulances, Fire Trucks
- Public – Buses, Trains, Railways, Subways
- Commercial – Boats, Heavy Equipment, Limousines, Taxis, Vans
- Transportation - Freight Liners
- Aviation – Helicopters, Commercial and Private Aircraft

For more information on any of our products or services please

visit us on the Web at:

www.sentry-resellers.com

or

www.cctvsentry.com

 SENTRY SECURITY SYSTEMS INC.
C/O Door 201
44951 Co. Route 191
Wellesley Island, NY 13640 

1257 Midland Ave. Unit #1
Kingston, ON, K7P 2Y1 
Phone: 866.736.8796
Fax: 613.384.1733

Sentry SMD-N4 Mobile DVR - Specifications

SENTRY SMD-N4 SPECIFICATIONS	
Video Inputs	4 BNC In, B/W & Color Compatible
Video Out	1 BNC Video Out
Audio	2 BNC Audio Input, 1 BNC Audio Out
Video Compression	MPEG4
Display/Record Speed	25F/S/Ch (PAL). 30 F/S/Ch (NTSC). Real-Time Video Display and Record
Alarm In/Out	4 Sensor Input Connections, 2 Alarm Output Connections. NO/NC Optional
Picture Quality	5 default Levels, 3 User-defined Levels
Record Mode	Continuous REC, Timer REC, Alarm REC, Motion Detect REC, Schedule REC
Motion Detection	Each channel up to 192 detection zone, sensitivity adjustable
HDD	Removable HDD, Plug and Play. 2.5" HDD supported
Network	10/100 RJ45, TCP/IP Protocol, IE browser supported
Remote	IR Remote Controller (full function) or wired keypad (optional)
Panel Operation	Playback, Stop, Pause, Display
Camera Power	1.5A, 12VDC Output for Cameras
Vehicle Sensor (Optional)	Brake—B Stop—S Warning—W Left—L Right—R Reverse—V Vehicle Speed Vehicle Speed calibration function, Km/h or Mile/h selectable
Structure	Case and HDD have special double shock-absorption technology
Power required	10V-30VDC Input Option, 10 Amp
Working Temperature	Working Temperature: -30°* to +50°. Humidity: < 90% (*with optional heater)
Weight	5 LBS / 2.3KG

For more information on any of our products or services please

visit us on the Web at:

www.sentry-resellers.com

or

www.cctvsentry.com


SENTRY SECURITY SYSTEMS INC.
 C/O Door 201
 44951 Co. Route 191
 Wellesley Island, NY 13640 
 1257 Midland Ave. Unit #1
 Kingston, ON, K7P 2Y1
 Phone: 866.736.8796
 Fax: 613.384.1733 